


Tri-Hole Stripping Tool

Part Number: SSF-TRIHOLE



The Cleerline™ Tri-Hole Fiber Optic Stripping Tool has three openings, allowing preparation of traditional fibers with up to a 3.0 mm jacket.

All stripping surfaces are quality manufactured to precise tolerances to ensure clean, smooth strips every time. Compliant thermoplastic elastomer handle grips. Factory set blade notches require no adjustment & will not scratch or nick the fiber.



FEATURES AND BENEFITS

- Compatible with traditional fibers with up to a 3.0 mm outer diameter
- Includes cleaning brush for maintenance.

APPLICATIONS

- Preparing Traditional (non-SSF™) fibers for termination/splicing
- Removing 600 µm - 3.0 mm jackets from SSF™ or traditional fibers

SPECIFICATIONS	
Compatible Cables	Traditional Fiber Optic Cables
Max Jacketed Cable Diameter	3.0 mm
Number of Stripping Openings	3
Openings	<ul style="list-style-type: none">• 1.6 - 3.0 mm --- 600 - 900 µm: SSF™ & Traditional Fiber Jacket Removal• 600 - 900 µm --- 250 µm: Traditional Fiber Prep & SSF™ Fusion Splicing• 250 µm ---125 µm: Removal of SSF™ Polymer For Fusion Splicing ONLY

PART NUMBER	DESCRIPTION
SSF-TRIHOLE	Tri-Hole Fiber Optic Stripper